



[Name of Document] Specification

[Title of the Invention] GAS SUPPLYING APPARATUS FOR FUEL CELL

[Claims]

[Claim 1]

5 A gas-supplying apparatus for a fuel cell, including a
heat exchange means for exchanging heat between a supply gas
to be supplied to the fuel cell and an exhaust gas which is the
supply gas used in the fuel cell and then discharged therefrom,
and transferring the heat of the exhaust gas to the supply gas,
10 the gas-supplying apparatus comprising:

an exhaust gas compressing and feeding means disposed
between the fuel cell and the heat exchange means, for
compressing and feeding the exhaust gas.

15 [Claim 2]

The gas-supplying apparatus for a fuel cell according to
claim 1, further comprising a pressure control means disposed
downstream of the exhaust gas compressing and feeding means and
of the heat exchange means.

20

[Claim 3]

The gas-supplying apparatus for a fuel cell according to
claim 2, wherein the compress control means is controlled in
accordance with a request supply gas temperature of the fuel
25 cell.

[Claim 4]

The gas-supplying apparatus for a fuel cell according to claim 3, wherein the pressure control means controls that pressure of the downstream of the exhaust gas compressing and feeding means is increased if the temperature of the supply gas is less than a predetermined lower limit, and the pressure control means controls that the pressure of the downstream of the exhaust gas compressing and feeding means if the temperature of the supply gas is not less than a predetermined upper limit.

[Detailed Description of the Invention]

[0001]

[Technical Field to which the Invention Pertains]

The present invention relates to a gas-supplying apparatus in a fuel cell, which make use of heat in an effective manner by carrying out heat-exchange between a supply gas supplied into a fuel cell and an exhaust gas exhausted from the fuel cell.

[0002]

[Related Art]

A fuel cell (solid macromolecular type fuel cell) has recently drawn considerable attention as a power source of an electric vehicle etc., because of its cleanness and excellent energy efficiency. Since the fuel cell works at a temperature above the room temperature, a supply gas to be supplied to the

fuel cell is heated and the heat from an exhaust gas exhausted from the fuel cell is recovered. For example, Japanese Patent Laid-Open No. 7-176313 discloses a fuel cell system having a regenerative heat-exchanging apparatus, which carries out heat exchange between air supplied to the fuel cell (supply air) and exhaust air from the fuel cell, and which humidifies the supply air. According to the publication, the heat generated from the fuel cell can be effectively used.

[0003]

[Problem to be Solved]

However, in order to improve the efficiency of the fuel cell, much more effective utilization of the heat from the fuel cell has been desired. Also, it has been desired for effectively operating the fuel cell to vary, and preferably control, the temperature of the supply gas to be supplied to the fuel cell. In this case, it is preferred if the effective utilization of the heat and the temperature control of the supply gas can be realized with a simple configuration.

[0004]

In addition, in a fuel cell system having a configuration that the supply gas is compressed through a compressor, and the compressed gas is supplied to the fuel cell, the supply gas is compressed only in a low amount through the compressor when the load of the fuel cell is small and; therefore, the temperature of the supply gas is small. Accordingly, the heat exchanger should heat the supply gas in this case. On the other hand, since

the supply gas is heavily compressed when the fuel cell is heavily loaded, the temperature of the supply gas becomes large. In some cases, the temperature of the supply gas becomes higher than the operation temperature of the fuel cell (greater than
5 120°C). Consequently, the heat exchanger should heat or cool down the supply gas, resulting in a complication of the apparatus. For this reason, it has been desired to develop a gas-supplying apparatus, which can control the temperature of the gas supplied to the fuel cell with a simple configuration.

10 Accordingly, a main object of the present invention is to solve the above problem.

[0005]

[Means for solving the Problems]

We have conducted serious studies in light of the above
15 problem, we have accomplished the present invention considering the heat generation during the course of the compression through the compressor and the layout of various related devices. Specifically, according to claim 1 of the present invention, a gas-supplying apparatus in a fuel cell,
20 which includes a heat exchange means for exchanging heat between a supply gas to be supplied to the fuel cell and an exhaust gas which is the supply gas used in the fuel cell and discharged therefrom, and transferring the heat of the exhaust gas to the supply gas, the gas-supplying apparatus comprises
25 an exhaust gas compressing and feeding means disposed between the fuel cell and the heat exchange means, for compressing and

feeding the exhaust gas.

With this structure, both the supply gas and the exhaust gas discharged from the fuel gas and reaching the exhaust gas compressing and feeding means are sucked by the exhaust gas sucking means. The exhaust gas at the discharge side of the exhaust gas compressing and feeding means is compressed to a pressure higher than that at the sucking side (sucking pressure). In this compression, the temperature of the exhaust gas is increased. Then, the exhaust gas is supplied to the heat exchange means, and its heat is exchanged by that of the supply gas, thereby heating the supply gas. In this case, the heat of the exhaust gas is transferred to the supply gas.

[0006]

According to claim 2 of the present invention, in the above invention, a pressure control means is disposed downstream of the exhaust gas compressing and feeding means and the heat exchange means.

With this configuration, when the pressure of the gas downstream of the compressor (discharge pressure) is increased by the control valve, the temperature of the exhaust gas can be increased accordingly. Conversely, if the discharge pressure is decreased by the control valve, the degree of increasing the temperature can be decreased. Specifically, the range of increasing the temperature of the gas at the side downstream of the compressor can be varied. The exhaust gas in which the range of increasing the temperature is variable is

heat-exchanged with the supply gas through the heat exchanger to heat the supply gas. In the case where the controller is composed of a pressure control valve such as a butterfly valve, the pressure at the downstream of side can be adjusted to be
5 decreased if the opening degree of the valve is decreased, while such a pressure can be adjusted to be large if the opening degree of the valve is increased.

[0007]

According to claim 3 of the present invention, in the above
10 invention, the compress control means is controlled depending on temperature of the supply gas requested by the fuel cell.

With this structure, the temperature of the supply gas to be supplied to the fuel cell can be made an appropriate one.

[0008]

15 According to claim 4 of the present invention, in the structure of claim 3, if the temperature of the supply gas is lower than a predetermined lower-limit temperature, the pressure control means controls such that the pressure of the downstream of the exhaust gas compressing and feeding means is
20 increased. On the other hand, if the temperature of the supply gas is equal to/higher than an upper-limit temperature, the pressure control means controls such that the pressure of the downstream of the exhaust gas compressing and feeding means is decreased.

25 Specifically, if the pressure of the downstream of the exhaust gas compressing and feeding means is increased, then

the temperature of the exhaust gas is increased. As a result, the amount of the heat exchange performed by the heat exchange means is increased, thus increasing the temperature of the supply gas. Meanwhile, if the pressure of the downstream of the exhaust gas compressing and feeding means is decreased, then the temperature of the exhaust gas is decreased. As a result, the amount of the heat exchange performed by the heat exchange means is decreased, thus decreasing the temperature of the supply gas. Accordingly, with the structure, if being less than a predetermined lower-limit temperature, the temperature of the supply gas can be increased. On the other hand, if being equal to/more than a predetermined upper-limit temperature, the temperature of the supply gas can be decreased. Consequently, it is possible to regulate the temperature of the supply gas to a range from the predetermined lower-limit to upper-limit temperatures. Note that the predetermined lower-limit to upper-limit temperatures can be defined appropriately, depending on the type of a fuel cell or operating conditions.

[0009]

[Description of the Preferred Embodiments]

Embodiments of the gas-supplying apparatus in the fuel cell according to the present invention will now be described by referring to the attached drawings.

[0010]

First Embodiment

The gas-supplying apparatus in the fuel cell according to the first embodiment will be described herein below.

In the following explanation which demonstrates the first embodiment, FIGS. 1 to 3 are used for the reference, wherein
5 FIG. 1 totally shows a fuel cell system including a gas-supplying apparatus in the fuel cell according to the present invention; FIG. 2 is a schematic view illustrating the configuration of the fuel cell in FIG. 1; and FIG. 3 is a graph showing the temperature-increasing profile in the compressor
10 shown in FIG. 1.

[0011]

A fuel cell system FCS shown in FIG. 1 is an electric power generation system based on a fuel cell 1. The fuel cell system FCS is mainly composed of the fuel cell 1, an air-supplying
15 apparatus 2, a hydrogen-supplying apparatus 3, and the like. The gas-supplying apparatus GS (GS1) is composed of the air-supplying apparatus 2, the hydrogen supplying apparatus 3, and a control unit 4.

[0012]

20 As shown in FIG. 2, the fuel cell 1 is divided into a cathode side (an oxygen pole side) and an anode side (a hydrogen pole side) across an electrolyte membrane 1c. Electrodes containing a platinum series catalyst are provided on both sides to form a cathode electrode 1b and an anode electrode 1d,
25 respectively. As the electrolyte membrane 1c, a solid macromolecular membrane such as a perfluorocarbon sulfonic

acid membrane, which is a proton-exchange membrane, is used. The electrolyte membrane 1c has a plurality of proton exchanging groups in the molecule thereof, and a low specific resistance not more than 20 .OMEGA.-proton at the normal
5 temperature when it has a saturated moisture content, acting as a proton-conductive electrolyte. The catalyst contained in the cathode 1b is a catalyst in order to produce oxygen ions from oxygen, and the catalyst contained in the anode 1d is a catalyst in order to produce protons from hydrogen.

10 [0013]

A cathode side gas passage 1a which allows a supply gas A as an oxidant gas for passing therethrough is provided outside the cathode electrode 1b, while an anode side gas passage 1e which allows hydrogen H to be supplied as a fuel gas for passing
15 therethrough is provided outside the anode electrode 1d. An inlet and outlet of the cathode side gas passage 1a are connected to the air-supplying apparatus 2, and an inlet and outlet of the anode side gas passage 1d are connected to the hydrogen-supplying apparatus 3. The configuration of the fuel
20 cell 1 shown in FIG. 2 is schematically shown as a single cell, but an actual fuel cell 1 is made up of a laminate with approximately 200 single cells laminated. Since the fuel cell heats up due to electrochemical reaction during the course of the power generation, the fuel cell 1 has a cooler (not shown)
25 which cools the fuel cell 1.

[0014]

In the fuel cell 1, when the supply air A is supplied to the cathode side gas passage 1a and the supply hydrogen H is supplied to the anode side gas passage 1e, hydrogen is ionized due to the catalyzation at the anode electrode 1d to produce
5 protons, which then move within the electrolyte membrane 1c to reach the cathode electrode 1b. The protons reaching the cathode electrode 1b are readily reacted with the oxygen ions produced from the oxygen contained in the supply air A to produce water. The supply air A containing the water thus
10 produced is discharged from the outlet at the cathode side of the fuel cell 1 as exhaust air Ae, which contains a large amount of moisture). Electron e^- are produced at the anode electrode 1d at the time of ionizing hydrogen, the resulting electrons e^- reach the cathode electrode 1b via an external load M such
15 as a motor.

[0015]

As shown in FIG. 1, the air-supplying apparatus 2 making up the gas-supplying apparatus GS1 in the fuel cell is composed mainly of an air cleaner 21, a heat exchanger 22, a humidifier
20 23, a compressor 24, a pressure control sensor 25, an airometer (flow sensor) Q, thermo-sensors T1 and T2, a humidity sensor H, and the like.

[0016]

The air cleaner 21 is composed of a filer (not shown), and
25 the like, and filtrates the air supplied to cathode electrode side of the fuel cell 1 (supply air A) to thereby remove dusts

contained in the supply air A.

[0017]

The heat exchanger 22 (as an apparatus) is composed of a plate type heat exchanger or a shell and tube type heat exchanger possessing passages at a low temperature fluid side and a high temperature side (not shown), and performs heat exchange between the air compressed through the compressor 24 (exhaust air Ae) and the supply air A having been filtered through the air cleaner 21. The supply air A is heated through the heat exchanger 22 and then is introduced into the fuel cell 1. The fuel cell 1 is operated at a temperature from about 80 to 90°C. For this reason, the temperature-controlled supply air A controlled to be from 60 to 75°C is introduced into the fuel cell 1. The temperature control of the supply air A will be described fully later on.

[0018]

The humidifier 23, which is one of a carburetor, is composed of Venturi tubes (capillary tubes), a water-storage tank, a siphon which connects the Venturi tubes and the water-storage tank etc. (not shown), the water stored in the water-storage tank is pumped by the Venturi action and is sprayed to humidify the supply air A. Into the siphon tube is inserted a needle which is driven by a stepping motor to control the flow amount of the water flowing through the siphon tube (the needle and the siphon tube making up a needle valve). As described above, the humidification of the supply air A is to

humidify the fuel cell 1 thereby preventing the drying of the electrolyte membrane 1c shown in FIG. 2. If the electrolyte membrane 1c is dried, the migration of the protons is inhibited, lowering the electromotive force. On the other hand, if the fuel cell 1 is humidified in excess, the cathode side gas passage 1a shown in FIG. 1 and/or diffusion layers (not shown) are soaked in water, leading to decrease in the electromotive power. The humidifier 23 may be comprised of a water-permeable membrane.

[0019]

The compressor 24 (means for pressing in the exhaust gas) is composed of a super charger (volume type compressor), a motor which drives the super charger (not shown), and the like, and the compressor 24 sucks the supply air A which has been used as the oxidant gas in the fuel cell 1, i.e., the exhaust air Ae discharged from the cathode pole side of the fuel cell 1, and deliveries it to the later heat exchanger 22. By sucking the supply air A, the compressor 24 plays a role in operating the fuel cell 1 through a negative pressure (pressure not higher than the atmospheric pressure). The compressor also adiabatically compresses the exhaust air Ae to raise the temperature of the exhaust air, whereby the exhaust air Ae having been heated up is used as a heat source for heating the supply air A.

[0020]

The pressure control valve (pressure controller) 25 is

composed of a butterfly valve and a stepping motor (not shown),
and the like, and it controls the pressure of the exhaust air
Ae out of the compressor (discharge pressure) by decreasing or
increasing the opening of the pressure control valve 25. When
5 the opening of the pressure control valve 25 is decreased, the
discharge pressure from the compressor 24 is increased and,
accordingly, the range of increasing the temperature of the
exhaust air Ae is increased. Conversely, when the opening of
the pressure control valve 25 is increased, the discharge
10 pressure from the compressor 24 is decreased, and accordingly,
the range of increasing the temperature of the exhaust air Ae
is decreased.

[0021]

The airometer Q is composed of a differential pressure
15 type flow meter etc., and it detects the flow amount of the
supply air A after flowing through the air cleaner 21 and sends
the detected signal to the controller 4.

[0022]

The thermo-sensor T1 is composed of a thermister, etc.,
20 and it detects the temperature of the supply gas A at the inlet
of the fuel cell 1 at the cathode side, which is sent to the
controller 4.

[0023]

The thermo-sensor T2 is composed of a thermister etc.,
25 similar to the thermo-sensor T1, and it detects the temperature
of the exhaust air Ae at the outlet of the compressor 24, which

is sent to the controller 4.

[0024]

The humidity sensor H is composed of a macromolecular type humidification sensor, etc., and it detects the humidity of the supply gas A at the inlet of the fuel cell 1 at the cathode side, which is sent to the controller 4.

[0025]

As shown in FIG. 1, the hydrogen-supplying apparatus 3 is composed of a hydrogen gas cylinder 31, a regulator 32, a hydrogen-circulating pump, a three-way valve 34, and the like.

[0026]

The hydrogen gas cylinder 31 is composed of a high-pressure hydrogen bottle (not shown) and it stores the supply hydrogen gas H to be introduced into the anode pole side of the fuel cell 1. The supply hydrogen H to be stored is pure hydrogen having a pressure of from 15 to 20 MpaG (150-200 kg/cm.^{sup.2}G). It is noted that the hydrogen gas cylinder 31 may be a type having a built-in hydrogen-occlusion alloy which stores hydrogen at a pressure of approximately 1 MpaG (10 kg/cm.^{sup.2}G).

[0027]

The regulator 32 is composed of a diaphragm, a pressure-adjusting spring (not shown), etc. and is a pressure controller which decreases the pressure of the supply hydrogen stored at a high pressure to a prescribed level so that the supply hydrogen H may be utilized at a constant pressure. Taking

the atmospheric pressure as the reference pressure to be introduced into the diaphragm, the regulator 32 can decrease the pressure of the supply hydrogen H stored in the hydrogen gas cylinder 31 to a level near the atmospheric pressure. Taking
5 the pressure of the negative pressure portion of the air-supplying apparatus 2 which is operated at a negative pressure as a reference pressure to be introduced into the diaphragm, the pressure of the supply hydrogen H stored in the hydrogen gas cylinder 31 can be decreased to a pressure near
10 the pressure of the corresponding negative pressure portion. In the first embodiment, since the hydrogen-supplying apparatus 3 is operated at a negative pressure not higher than the atmospheric pressure, the pressure at the intake side of the compressor 2 of the air-supplying apparatus 2 is input as
15 the reference pressure. By operating the hydrogen-supplying apparatus 3 at a negative pressure, the external leakage of the flowing hydrogen can be prevented, which improve the fuel efficiency.

[0028]

20 The hydrogen-circulating pump 33 is composed of an ejector (not shown), etc., and it utilize a flow of the supply hydrogen H towards the anode side of the fuel cell 1 to suck the supply hydrogen H having been used in the fuel cell 1, i.e., the exhaust hydrogen He, which is discharged from the anode side of the fuel
25 cell 1 and flows through a three-way valve 34, and to circulate it. The reason why the exhaust hydrogen is circulated and used

is that the supply hydrogen H is pure hydrogen stored in the hydrogen gas cylinder 31.

[0029]

The three-way valve 34 is composed of a passage switcher
5 (not shown), etc., and it switches the passage of the exhaust hydrogen He to the discharge position or circulation position. When the three-way valve 34 is switched to the discharge position, the exhaust hydrogen He is discharged out of the system of the hydrogen-supplying apparatus 3. When the
10 three-way valve 34 is switched to the circulation position, the exhaust hydrogen He is introduced into a hydrogen circulation pump 33.

[0030]

The controller 4 which makes up the gas-supplying
15 apparatus GS1 in the fuel cell is composed of CPU, memories, I/O interface, A/D converter, bus, etc., (not shown). The controller 4 totally controls the fuel cell system FCS. The controller 4 also controls the flow amount, temperature and the humidity of the supply air A to be supplied to the fuel cell
20 1. The controller 4 receives the detected signals from sensors Q, T1, and T2. Also, the controller 4 sends the control signals to the humidifier, to the compressor 24 and to the pressure control valve. The control of the flow amount, temperature and the humidity of the supply air A will now be described.

25 [0031]

(1) With regard to the control of the flow amount, the

controller 4 sets a target flow amount of the supply air A to be required through a map etc., on the basis of the output demand signal from means for adjusting output such as an accelerator pedal (not shown). When the target flow amount is increased, the controller 4 produces a control signal so as to increase the discharge amount from the compressor 24 (revolution number of the motor) and send it to the compressor 24. On the other hand, when the target flow amount is decreased, the controller 4 produces a control signal so as to decrease the discharge amount from the compressor 24 (revolution number of the motor) and send it to the compressor 24. At this time, a feed back control is performed so that the deviation between the detected signal from the airometer Q and the target flow amount becomes zero.

[0032]

(2) With regard to the temperature control, the controller 4 the temperature of the supply air A to be the target temperature ranging from 60C° (the lower limit of the prescribed temperature) to 75C° (the upper limit of the prescribed temperature) on the basis of the detected signal from the thermo-sensor T1 by means of the opening of the pressure control valve 25 through the stepping motor. Specifically, when the temperature of the supply air A is or will be increased to be not lower than the target temperature, the controller 4 produces a control signal so as to drive the stepping motor in such a manner as to decrease the opening of the pressure control

valve, and send the produced signal. This decreases the discharge amount from the compressor 24, decreasing the temperature of the exhaust gas Ae, which in turn, decreases the heat exchange amount in the heat exchanger 22 to thereby
5 decrease the temperature of the supply air A. On the other hand, when the temperature of the supply air A is or will be decreased to be not higher than the target temperature, the controller 4 produces a control signal so as to drive the stepping motor in such a manner as to increase the opening of the pressure
10 control valve, and send the produced signal. This increases the discharge amount from the compressor 24, increasing the temperature of the exhaust gas Ae, which in turn, increases the heat exchange amount in the heat exchanger 22 to thereby increase the temperature of the supply air A. At this time, a
15 feed back control is performed so that the deviation between the detected signal from the thermometer T1 and the target temperature becomes zero. Irrelevant to the opening of the pressure control valve 25, the compressor 24 actuates to supply the supply air A in a target flow amount into the fuel cell 1.

20 [0033]

As a fail-safe mechanism, when the detected signal from the thermo-sensor T2 becomes higher than a given level (not lower than 150°C), in order to protect the compressor 24, etc., the controller 4 produces a control signal for increasing the
25 opening of the pressure control valve 25 and/or a control signal for decreasing the discharge amount from the compressor 24 and

send it/them. This decreases the temperature at the discharge side of the compressor 24 to thereby protect the compressor 24.

[0034]

FIG. 3 shows a relationship between the pressure ratio
5 (discharge pressure/intake pressure) of the compressor 24 and
the range of increasing the temperature of the exhaust air Ae
[$T = (\text{temperature at the discharge side}) - (\text{temperature at intake side})$], i.e., temperature increasing characteristics. As seen
from this figure, it can be understood that when the pressure
10 ratio is increased (or decreased), the range of increasing the
temperature is increased (or decreased). Consequently, by
controlling the pressure control valve 25, the temperature of
the exhaust air Ae at the discharge side of the compressor 24
can be controlled and, thus, the supply air A, which will be
15 heat-exchanged, can be controlled.

[0035]

(3) With regard to the humidity control, the controller
4 controls the humidity of the supply air A to be supplied into
the inlet of the fuel cell 1 at the cathode pole side so as to
20 be a target humidity on the basis of the detected signal from
the humidity sensor H by controlling the opening of the needle
valve of the humidifier 23 through a stepping motor.
Specifically, when the humidity of the supply air is or will
be increased to be higher than the target humidity, the
25 controller 4 produces a control signal such as to drive the
stepping motor in such a manner as to decrease the opening of

the needle valve and send the produced control signal. This decreases the amount of moisture flowing through the needle valve, decreasing the humidify of the supply air A. On the other hand, when the humidity of the supply air is or will be decreased
5 to be higher than the target humidity, the controller 4 produces a control signal such as to drive the stepping motor in such a manner as to increase the opening of the needle valve and send the produced control signal. This increases the amount of moisture flowing through the needle valve, increasing the
10 humidify of the supply air A. At this time, a feedback control is performed so that the deviation between the detected signal from the humidity sensor H and the target humidity becomes zero.

[0036]

Next, one example of the operation of the gas-supplying
15 apparatus GS1 in the fuel cell according to the first embodiment, which has been described, will now be described by referring to FIG. 4 (also referring to FIGS. 1 to 3 as occasion may demand).

FIG. 4 shows a control flow of a gas-supplying apparatus
20 in the fuel cell. In this control flow and the description thereof, the symbol T1 indicates the temperature detected by the thermo-sensor T1, and the symbol T2 indicates the temperature detected by the thermo-sensor T2.

[0037]

25 Usual Treatment: In Step S1, the controller 4 judges the temperature T2 of the exhaust air Ae at the discharge side of

the compressor 24. If the temperature T2 is lower than 150°C., the controller 4 judges the temperature T1 of the supply air A at the inlet of the fuel cell 1 of the cathode pole side in Step S2. If the temperature T1 is lower than 60°C., which is
5 too low, the controller 4 closes the pressure control valve 25 one degree (S3). This increases the temperature T2 of the exhaust air Ae at the discharge side of the compressor 24 and, at the same time, increases the temperature T1 of the supply air A whose temperature is heat-exchanged with that of the
10 exhaust air is also increased (with regard to the flow amount of the supply air A, it is controlled so as to be the target flow amount irrelevant to the opening of the pressure control valve [and so forth]). Even if the temperature T1 of the supply air A is still lower than 60°C when being returned to step S2
15 via step S4 and step S1, the pressure control valve 25 is closed 1 degree in step S3. This further increases the temperature T1 of the supply air A.

[0038]

When the temperature T1 of the supply air A is not lower
20 than 60°C, the above-mentioned step S2, the controller 4 judges whether or not the temperature T1 of the supply air A is equal to or higher than 75°C in step S5. If the temperature T1 is higher than 75°C, which is too high, the pressure control valve 25 is opened 1 degree (S6). This decreases the temperature T2
25 of the exhaust air Ae at the discharge side of the compressor 24 and, at the same time, decreases the temperature T1 of the

supply air A which is heat-exchanged with the exhaust air Ae.
If the temperature T1 of the supply air A is still higher than
75°C when being returned to step S5, the pressure control valve
25 is further opened another 1 degree, which further decreases
5 the temperature T1 of the supply air A.

[0039]

If the temperature T1 of the supply air A at the inlet of
the fuel cell 1 of the cathode pole side is lower than 75°C in
step 5, the controller 4 is returned to the position between
10 step S3 and step S4 of the main routine. At the normal situation,
these treatments are repeated. It is noted that the term "end
of treatment" in step 4 indicates, for example, the situation
where the operation of the fuel cell system FCS is stopped.

[0040]

15 Treatment at High Temperature: If the temperature T2 of
the exhaust air Ae at the discharge side of the compressor 24
is not lower than 150°C, the controller 4 opens the pressure
control valve 25 1 degree at step S7 in order to protect the
compressor 24 etc. This decreases the pressure and the
20 temperature T2 of the exhaust air Ae at the discharge side of
the compressor 24. If the temperature T2 of the exhaust air Ae
at the discharge side of the compressor 24 is not lower than
140°C in step S8, the controller 4 is returned to step 7 to
further open the pressure control valve 25 another 1 degree.
25 This further decreases the temperature T2 of the exhaust air
Ae. When the temperature T2 of the exhaust air Ae at the

discharge side of the compressor 24 becomes lower than 140°C in step S8, which is sufficiently lowered, the controller 4 is returned to the position between step S3 and step S4 of the main routine. The reason why the treatment at a high temperature up to 140°C is that the temperature T2 of the exhaust air Ae exceeding 150°C should be sufficiently cooled down to protect the compressor 24, etc. Also, such a treatment is carried out to prevent from being frequently shifted to the treatment at a high temperature from the viewpoint of the control.

10 [0041]

As described above, according to the gas-supplying apparatus GS in the fuel cell according to the first embodiment, the temperature control of the supply air A can be surely carried out through a very simple configuration that the pressure control valve 25 is provided and it is opened or closed. Also, according to this embodiment, heat can be effectively utilized. Furthermore, the heat exchanger 22 may always transmit the heat possessed by the exhaust air Ae to the supply air A to heat the supply air A, the simple configuration can be designed. It is noted that when the humidity is decreased in each of the above-mentioned steps, the controller 4 may increase the amount of moisture to be injected to carry out humidification. Also, if the target flow amount is increased (or decreased), the controller 4 may increase (or decrease) the revolution number of the motor to be normalized. It is also noted that in the hydrogen-supplying apparatus, the

temperature control and the humidity control are carried out.

[0042]

Second Embodiment

Next, a gas-supplying apparatus in the fuel cell according
5 to the second embodiment of the present invention will now be
described. Elements, parts, and the like identified with those
of the first embodiment have the same numerals or symbols and
their descriptions will be omitted.

FIG. 5 shows a control flow of a gas-supplying apparatus
10 in the fuel cell according to the second embodiment of the
present invention.

[0043]

In a gas-supplying apparatus GS2 in the fuel cell
according to the second embodiment, a water-permeable type
15 humidifier utilizing hollow fiber membrane (not shown) is used
as the humidifier 23. The hollow fiber membrane comprises
hollow fibers each having a hollow passage, a diameter ranging
from 1 to 2 mm and a length of several ten cm. The humidifier
23 is composed of two hollow fiber membrane modules each
20 accommodated within a hollow container, each module comprising
a bundle of several thousands of hollow fibers, piping which
connects these two hollow fiber membrane modules in parallel,
switchers (switching means) for switching these two hollow
fiber membrane modules depending upon the flow amount and the
25 humidity of the supply air, such as an electromagnetic valve
and a controller for the electromagnetic valve (all being not

shown). In this embodiment, the controller for the electromagnetic valve is included in the controller 4.

[0044]

A packing ratio of the hollow fiber membrane in each hollow
5 fiber membrane module is from 40 to 60% relative to the cross-section of the hollow container. The hollow fiber membrane module is configured so that the exhaust air Ae flows from one end of the hollow passage and is discharged from another end. Also, the hollow fiber membrane module is
10 configured so that the supply air A flows through the gaps among the hollow fibers and is then discharged. Specifically, the hollow fiber membrane module is configured not so as to mix the supply air A with the exhaust air Ae. On the other hand, the hollow fiber membrane module possesses a plurality of capillary
15 tubes from its internal surface to the external surface each having a diameter of several nm. In the capillary tubes, the vapor pressure is decreased, easily resulting in condensation of the moisture. The condensed moisture is sucked out due to the capillary phenomenon and is permeated through the hollow
20 fiber membrane. Consequently, when the exhaust air Ae containing a large amount of moisture produced in the fuel cell 1 flows through the hollow passage, the moisture is condensed on the internal surface of the hollow passage, and the condensed moisture humidifies the supply air A which is relatively dried
25 and flows through the gaps among the hollow fibers. It is also possible that the supply air A flows through the hollow passage

side and the exhaust air Ae flows through the gaps among the hollow fibers.

[0045]

The humidifier 23 is configured so that when the flow
5 amount of the supply air is small, the switcher switches the
hollow fiber membrane modules so as to only use one hollow fiber
membrane module, and when the flow amount of the supply air is
large, the switcher switches the hollow fiber membrane modules
so as to use both hollow fiber membrane modules. The switching
10 of the hollow fiber membrane module is due to the humidification
characteristic of the hollow fiber membrane module that the
humidification performance of the hollow fiber membrane module
is decreased if the follow amount of the supply air A and that
of the exhaust air Ae are too small or too large. The timing
15 for switching the hollow fiber membrane modules or such is
decided by the detected signal from the airmometer Q and the
detected signal from the humidity sensor H.

[0046]

The humidifier 23 utilizing the hollow fiber membrane
20 modules also serves as a heat exchanger which exchanges the heat
possessed by the supply air A and that possessed by the exhaust
air Ae. Consequently, unlike the first embodiment, the
gas-supplying apparatus according to this embodiment has no
separate heat exchanger.

25 [0047]

The gas-supplying apparatus GS2 according to the second

embodiment having the same configurations as those of the first embodiment, except for the portion of the heat exchanger and the humidifier can surely control the temperature of the supply air A only by the simple configuration of opening or closing
5 the pressure control valve 25. Also, with regard to the utilization of heat, the apparatus according to this embodiment has similar characteristic as those of the first embodiment. Furthermore, in the gas-supplying apparatus GS2 according to the second embodiment, which can effectively utilize a large
10 amount of the moisture contained in the exhaust air Ae, the moisture for humidification is not required to be stored, or the amount of the moisture to be stored can be minimized. Also, the humidification of the supply air A can be carried out in a uniform manner.

15 [0048]

Third Embodiment

Next, a gas-supplying apparatus in the fuel cell according to the third embodiment of the present invention will now be described. Elements, parts, and the like identified with those
20 of the first embodiment have the same numerals or symbols and their descriptions will be omitted.

FIG. 6 shows a control flow of a gas-supplying apparatus in the fuel cell according to the third embodiment of the present invention.

25 [0049]

In a gas-supplying apparatus GS3 in the fuel cell

according to the third embodiment, the moisture condensed in the heat exchanger 22 is utilized as the moisture for the humidification in the humidifier 23. Accordingly, the heat exchanger 22 according to the third embodiment has a catch tank 5 22a which captures the moisture condensed and separated from the exhaust air Ae, and a water feed pipe 23, which supplies the condensed moisture to a water storage tank (not shown). The catch tank 22a may also serve as the water storage tank. It is noted that the heat exchanger which condenses the water is 10 generally utilized in an air conditioner.

[0050]

The gas-supplying apparatus GS3 according to the third embodiment having the same configurations as those of the first embodiment, except for supplying of the condensed moisture in 15 the heat exchanger 22 to the humidifier 23 can surely control the temperature of the supply air A only by the simple configuration of opening or closing the pressure control valve 25. Also, the gas-supplying apparatus GS3 according to the third embodiment can effectively utilize a large amount of the 20 moisture contained in the exhaust air Ae discharged from the cathode side of the fuel cell 1 as in the second embodiment.

[0051]

Fourth Embodiment

Next, a gas-supplying apparatus in the fuel cell according 25 to the fourth embodiment of the present invention will now be described. Elements, parts, and the like identified with those

of the first to the third embodiments have the same numerals or symbols and their descriptions will be omitted.

FIG. 7 shows a control flow of a gas-supplying apparatus in the fuel cell according to the fourth embodiment of the present invention.

[0052]

A gas-supplying apparatus GS4 in the fuel cell according to the third embodiment possesses the same heat exchanger 22 as in the third embodiment, i.e., the heat exchanger 22 having a catch tank 22a which captures the moisture condensed and separated from the exhaust air Ae. The humidifier 23 used in this embodiment is the same as the humidifier used in the second embodiment. Specifically, the humidifier 23 used in this embodiment switches two hollow fiber membrane modules to be used depending upon the flow amount and the humidity of the supply air A. Furthermore, according to the fourth embodiment of the present invention, the gas-supplying apparatus has an auxiliary humidifier 23'. The auxiliary humidifier 23' used herein is the same as the humidifier in the third embodiment and the condensed moisture is supplied from the catch tank 22a via the water storage tank (not shown). Any other configurations of the gas-supplying apparatus of this embodiment are the same as those of the first embodiment, and a pressure control valve 25 which controls the pressure of the exhaust air Ae discharged from the compressor 24 is provided after the heat exchanger 22.

[0053]

It is noted that the auxiliary humidifier 23' is used, for example, in the case where the supply air A cannot be sufficiently humidified i.e., the flow amount of the supply air
5 A is sharply increased or the fuel cell system FCS is started.

[0054]

The gas-supplying apparatus GS4 according to the fourth embodiment can surely control the temperature of the supply air A only by the simple configuration of opening or closing the
10 pressure control valve 25 as in the first embodiment. Also, in the gas-supplying apparatus GS4 according to the fourth embodiment, since the humidifier serves as the heat exchanger in which the heat possessed by the exhaust air Ae is transmitted to the supply air A in addition to the heat exchanger, the
15 gas-supplying apparatus GS4 can effectively utilize the heat possessed by the exhaust air Ae. What is more, the moisture contained in the exhaust air Ae, which has not been used in the humidifier 23, can be recovered in the heat exchanger 22 to be used in the humidifier 23'. Consequently, the gas-supplying
20 apparatus according to this embodiment can effectively utilize the moisture, and can securely humidify the supply air A even when the flow amount of the supply air A is changed.

[0055]

As described above, according to the present invention,
25 the heat generated from the fuel cell can be effectively utilized and, at the same time, the heat generated during the

course of pumping (compressing) the exhaust gas through the compressor can also be effectively utilized in the present invention. Consequently, the heat efficiency can be improved. Furthermore, since the heat exchanger can only heat the supply
5 air always utilizing the exhaust gas as a heat source, the gas-supplying apparatus has a simple configuration and has improved reliability. Moreover, since the compressor for the exhaust gas is provided downstream of the fuel cell, the work power can be decreased in comparison with the case where it is
10 provided upstream the fuel cell. Specifically, the power (electric power consumption) can be decreased in comparison with the compressor provided upstream the fuel cell. Also, the power output from the fuel cell can be effectively utilized without sharing with the compressor for the exhaust gas. When
15 the gas-supplying apparatus is applied to the fuel gas (hydrogen gas) side, the fuel gas side can be operated by a negative pressure. Consequently, the leakage of the fuel gas can be prevented.

[0056]

20 [Effects of the Invention]

With the invention of claim 1, it is possible to utilize heat generated from a fuel cell, as well as to utilize heat generated when an exhaust gas is compressed and fed by an exhaust gas compressing and feeding means. As a result, the
25 efficiency of a fuel cell can be enhanced. In addition, a heat exchanger can heat air by using an exhaust gas as a heat source

anytime, thereby making the structure of a gas supply apparatus in fuel cell simple. Also the reliability of the apparatus is improved. Since an exhaust gas compressing and feeding means is disposed downstream of the fuel cell, work load can be
5 decreased, compared to the case where the exhaust gas compressing and feeding means is disposed upstream of the fuel cell. In other words, Since an exhaust gas compressing and feeding means is disposed downstream of the fuel cell, power (consumption power) of the exhaust gas compressing and feeding
10 means can be decreased. Moreover, the power of the fuel cell can efficiently be used, because the power is not used by the exhaust gas compressing and feeding means. If this gas supply apparatus in a fuel cell is applied to the side of a fuel gas (hydrogen), then the system at the side of the fuel gas can work
15 under a negative pressure, thereby preventing a fuel gas to be leaked.

[0057]

With the invention of claim 2, discharge pressure of the exhaust gas compressing and feeding means is varied by a
20 pressure control means, and the temperature range of the exhaust gas is therefore varied. Also, the temperature range of the supply gas is exchanged by the exhaust gas can be varied. Consequently, it is possible to operate the fuel cell stably.

[0058]

25 With the invention of claim 3, the temperature of a supply gas to be supplied to a fuel cell is made proper, so that the

fuel cell operates automatically under the appropriate conditions.

[0059]

With the invention of claim 4, it is possible to control
5 the temperature of a supply gas to be supplied to a fuel cell
to a predetermined range. This enables a fuel cell to operate
under appropriate conditions.

[Brief description of the Drawings]

10 [FIG. 1]

FIG. 1 totally shows a fuel cell system including a
gas-supplying apparatus in the fuel cell according to the
present invention.

[FIG. 2]

15 FIG. 2 is a schematic view illustrating the configuration
of the fuel cell in FIG. 1.

[FIG. 3]

FIG. 3 is a graph showing the temperature-increasing
profile in the compressor shown in FIG. 1.

20 [FIG. 4]

FIG. 4 shows a control flow of a gas-supplying apparatus
in the fuel cell according to the first embodiment of the
present invention.

[FIG. 5]

25 FIG. 5 shows a control flow of a gas-supplying apparatus
in the fuel cell according to the second embodiment of the

present invention.

[FIG. 6]

FIG. 6 shows a control flow of a gas-supplying apparatus
in the fuel cell according to the third embodiment of the
5 present invention.

[FIG. 7]

FIG. 7 shows a control flow of a gas-supplying apparatus
in the fuel cell according to the fourth embodiment of the
present invention.

10

[Description of Reference Numerals]

GS (GS1, GS2, GS3, GS4) gas supply apparatus in fuel cell

FCS fuel cell system

A supply air (supply gas)

15 Ae exhaust air (exhaust gas)

1 fuel cell

2 air supplying apparatus

22 heat exchanger (heat exchange means)

24 compressor (exhaust gas compressing and feeding means).

20 25 compress control valve (pressure control means)

3 hydrogen supplying apparatus

4 control unit